



## MagnaPrint® Reflective 3R Range

### Ready to use high reflective ink

MagnaPrint® Reflective 3R Range has been designed to give excellent reflectivity and soft handle using micro glass beads.

The MagnaPrint® Reflective 3R Range consists of following products:

MagnaPrint® Reflective 3R Black  
MagnaPrint® Reflective 3R Silver

### Application

MagnaPrint® Reflective 3R Range can be applied by either rotary or screen printing. Screen mesh selection is dependent on the particle size which is approximately 60 microns; therefore, the mesh size should be 3x the maximum particle size.

MagnaPrint® Reflective 3R Range should be dried and cured for 2 - 2½ minutes at 165°C (330°F).

### SPECIFICATION



**FABRIC TYPES**  
Cotton / Poly Cotton blends



**MESH**  
24 - 43T (60 - 110)



**SQUEEGEE**  
Medium 65° Shore  
Rectangular



**STENCIL**  
Water resistant emulsion



**CURE TEMPERATURE**  
2 - 2½ minutes at 165°C  
(330°F)



**PIGMENT LOADING**  
Up to 3% MagnaPrint®  
Eco Pigments



**ADDITIVES**  
Retardant Gel, Softener TS



**STORAGE**  
In cool place properly closed:  
>5°C (40°F) <25°C (77°F)



**HEALTH & SAFETY**  
MSDS available upon  
request



**CLEAN UP**  
Wash off screen using water  
and mild detergent

All information is given in good faith but without warranty. They do not release you from testing our products as to their suitability for the intended processes and uses.