

TECHNICAL DATA SHEET

PRODUCT # TB-10

Tekbond TB-10 is a high solids acrylic copolymer pressure sensitive adhesive composed of 55-60% acrylic copolymers and 40-45% Water. It is not considered to be a hazardous material for humans, animals or plant life when used for its' intended purpose as a screen printing table adhesive.

Adhesive will clean up when wet with warm water. When dried a suitable cleaner must be used-Recommend Tekmar TBAR-Orange

DOT Shipping Information

No Restrictions

International Shipping Information

Harmonized Code Name: Other Acrylic Polymers in Primary Forms

Harmonized Code Number: 3906.90.6000

Shipping Information: Not considered Hazardous for Air, Ocean or

Ground Transportation

Physical Specifications

Base: Acrylic Polymer Solvents: None

Solids: Approx. 55-60% ODOR: Sweet Odor

Color: White pH: 6-7

Appearance: Opaque Freeze Point 32°f (0°c)

NOT FREEZE-NOT FREE/THAW STABLE

Viscocity: 250-400 cPs Optimal Temperature: 50° - 120° DEGREES F

(Brookfield)

F & DA: Conforms to CFR 175.105

SHIPPING MAILING
927 Indio Muerto St. P.O. Box 4700
Santa Barbara, CA 93103 USA Santa Barbara, CA 93140 USA

ATLANTA SHIPPING 879 Davis Drive Conyers, GA 30094 USA

Customer Line: 800/564-1096 • Phone: 805/965-0704 • Fax: 805/963-7794